

Tower Products, Inc., 2703 Freemansburg Ave., Easton, PA 18045
 Information Telephone Number: 1-800-527-8626 or 610-253-6206
For Chemical Spill Emergency - Call 1-800-424-9300

SECTION 1: PRODUCT INFORMATION

Product Name: **WEB CONDITIONER** (Premium Antistatic Web Conditioner)
 D.O.T. Designation: Cleaning Liquid. Not Regulated.
 U.N. Designation: Same as D.O.T.

SECTION 2: HAZARDOUS COMPONENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENT	CAS No.	% WT	OSHA PEL	ACGIH TLV-TWA	OTHER RATINGS	OSHA STEL
NONE						

SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 212 degrees F.
 Specific Gravity: (Water = 1) 1.015
 Vapor Pressure: (mmHG, calculated) N/A
 Melting Point: N/A
 Vapor Density: (Air = 1, calculated) N/A
 Solubility in Water: Dispersible
 pH of Concentrate: 7.5-8.5
 Viscosity: 200-500 CPS
 Appearance & Odor: Opaque Blue Liquid Emulsion with a slight odor.
 Maximum VOC Content: None
 Maximum VOC% : None

SECTION 4: FIRE AND EXPLOSION DATA

Flash Point (Tag Closed Cup Method): None
 Flammable Limits (Calculated): LEL: N/A UEL: N/A
 Extinguishing Media: CO2, Foam, Dry Chemical or Water Spray
 Special Fire-fighting Procedures: N/A
 Unusual Fire and Explosion Hazards: N/A

SECTION 5: REACTIVITY DATA

Stability: Stable
 Incompatibility: Avoid contact with acids, flammable liquids, organic halogens, aluminum and soft alloys.
 Hazardous Decomposition or Byproducts: None
 Hazardous Polymerization: Will not occur.
 Conditions to Avoid: Avoid contact with acids, flammable liquids, organic halogens, aluminum and soft alloys.

SECTION 6: HEALTH HAZARD DATA

Routes of Entry: Inhalation, Ingestion, Skin
 Health Hazards:
 Eye Contact: May lead to irritation.
 Skin Contact: May lead to dermatitis.
 Ingestion: May lead to vomiting.
 Carcinogenicity (NTP, IARC, OSHA): Components of this product have not shown any evidence of carcinogenicity.

Signs and Symptoms of Exposure: Overexposure may lead to dermatitis and eye irritation.

Medical Conditions Aggravated by Exposure: None known under recommended usage conditions.

Emergency and First Aid Procedures:

For Skin Contact: Flush with large volume of water for at least 15 minutes.

Get medical attention if necessary.

For Inhalation: Remove to fresh air. Get medical attention if necessary.

For Eye Contact: Flush with large volume of water for at least 15 minutes.

Get immediate medical attention.

For Ingestion: Give 3 glasses of water. Get immediate medical attention.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE/REGULATORY INFORMATION

Steps to be taken in case material is released or spilled:

(Minor Spills): Absorb material with ground clay, vermiculite, or similar absorbent material, then place into containers for removal.

(Major Spills): Dike and contain spill. Eliminate potential sources of ignition, and shut off source of spill if possible. Remove liquid by chemical vacuum, absorbent, or other safe and approved method and place into containers for legal disposal. Flush area with water to remove residue, and remove flushed solutions as above.

(Waste Disposal Method): Dispose of all waste in accordance with federal, state and local regulations.

Regulatory Information:

Reportable quantity (RQ) EPA Regulation 40CFR302 (CERCLA) Section 102: None.

EPA Regulation 40CFR372 (SARA 313): None.

Precautions to be Taken in Handling and Storing: Ventilation in work area should be sufficient to maintain atmosphere with vapor level below lowest listed TLV in Section 2. If TLV's are exceeded, use a respirator with appropriate NIOSH approved cartridges or supplied air equipment. **Keep container tightly closed to maintain proper quality.** Empty containers can be hazardous. Store above 32 degrees F. Freezable.

HMIS: Health Hazard: **1**

Flammability: **0**

Reactivity: **0**

Personal Protection: **X**

SECTION 8: CONTROL MEASURES

Respiratory Protection: Not normally required; however, if vapor or mist is generated in confined or poorly ventilated area which causes the TLV's in Section 2 to be exceeded, then use a respirator with appropriate NIOSH approved cartridges or use supplied air equipment.

Ventilation: Local and mechanical exhaust recommended. Avoid open electrical sources near product vapor areas.

Protective Gloves: Impervious or chemical resistant gloves (consult safety equipment supplier).

Eye Protection: Chemical splash goggles recommended to protect against potential eye contact.

Other Protective Clothing and Equipment: Safety shoes and aprons recommended.

Work and Hygienic Practices: Do not take internally. Avoid skin contact and wash skin after using products. Do not eat, drink or smoke in work area. Keep away from children.

FOR MORE INFORMATION, CONSULT TOWER PRODUCTS, INC.

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIED IS MADE.