

Tower Products, Inc., 2703 Freemansburg Ave., Easton, PA 18045  
Information Telephone Number: 1-800-527-8626 or 610-253-6206  
**For Chemical Spill Emergency - Call 1-800-424-9300**

**SECTION 1: PRODUCT INFORMATION**

Product Name: **INFINITY WASH HMK UV** (FOGRA Approved UV/EB Wash)  
D.O.T. Designation: Cleaning Liquid. Not Regulated.  
UN Designation: Same as D.O.T.

**SECTION 2: HAZARDOUS COMPONENTS/IDENTITY INFORMATION**

HAZARDOUS COMPONENT	CAS No.	WT.	OSHA PEL	ACGIH TLV-TWA	OTHER RATINGS	OSHA STEL
Dipropylene Glycol Monomethyl Ether and proprietary non-hazardous surfactants and corrosion inhibitors.	34590-94-8	80-90	100ppm	100ppm		150ppm

**SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS**

Boiling Point: Initial BP 212 degrees F.  
Specific Gravity: (Water =1) 0.96  
Vapor Pressure: (mmHG, calculated) Less than 1 @ 68 degrees F.  
Melting Point: N/A  
Vapor Density: (Air =1) Less than 5  
Solubility in Water: Complete  
Appearance & Odor: Light colored liquid, ether solvent odor  
Maximum VOC Content: 7.12 lbs. per gallon (855 grams per liter)  
Maximum VOC%: 89%

**SECTION 4: FIRE AND EXPLOSION DATA**

Flash Point (Tag Closed Cup Method): 167 degrees F.  
Flammable Limits (Calculated): LEL: 1.1% UEL: N/A  
Extinguishing Media: Use dry chemical or carbon dioxide.  
Special Fire-fighting Procedures: Use self-contained breathing apparatus.  
Unusual Fire and Explosion Hazards: Combustible liquid. Upon combustion, the product may form carbon monoxide and other organic compounds. Product containers may rupture from vapor pressure when exposed to heat from fire.

**SECTION 5: REACTIVITY DATA**

**WARNING:** Spontaneous combustion may occur when solvent soaked combustible materials (paper, cotton, etc.) are allowed to stand in confined areas.  
Stability: Stable  
Incompatibility: Avoid strong oxidizing agents.  
Hazardous Decomposition or Byproducts: Carbon monoxide during combustion.  
Hazardous Polymerization: Will not occur.  
Conditions to Avoid: Avoid high heat sources, electrical and welding arcs, open flame and strong oxidizing agents.

**SECTION 6: HEALTH HAZARD DATA**

Routes of Entry: Inhalation, Ingestion, Skin  
Health Hazards (Acute): Overexposure may lead to central nervous system depression, leading to headaches, nausea and unconsciousness.

Health Hazards (Chronic): Overexposure in high concentrations may produce central nervous system depression.

Eye Contact: May lead to irritation.

Skin Contact: May lead to dermatitis.

Ingestion: May lead to vomiting.

Carcinogenicity (NTP, IARC, OSHA): Components of this product have not shown any evidence of Carcinogenicity.

Signs and Symptoms of Exposure: Overexposure may lead to dizziness, headaches, dermatitis and eye irritation.

Medical Conditions Aggravated by Exposure: Health studies have shown that many petroleum hydrocarbons pose potential health risks that vary from person to person. Minimize exposure to liquids, vapors, mists or fumes.

Emergency and First Aid Procedures:

For Skin Contact: Flush with large volume of water for at least 15 minutes.

Get immediate medical attention if necessary.

For Inhalation: Remove to fresh air. Get immediate medical attention.

For Eye Contact: Flush with large volume of water for at least 15 minutes. Get immediate medical attention.

For Ingestion: Get immediate medical attention. Do not induce vomiting.

## **SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE/REGULATORY INFORMATION**

Steps to be taken in case material is released or spilled:

(Minor Spills): Absorb material with ground clay, vermiculite, or similar absorbent material, and then place into containers for removal.

(Major Spills): Dike and contain spill. Eliminate potential sources of ignition, and shut off source of spill if possible. Remove liquid by chemical vacuum, absorbent, or other safe and approved method and place into containers for legal disposal. Flush area with water to remove residue, and remove flushed solutions as above.

(Waste Disposal Method): Dispose of all waste in accordance with federal, state and local regulations.

Regulatory Information: This information may be useful in complying with EPA Regulation 40CFR302 (CERCLA) Section 102 and EPA Regulation 40CFR372 (SARA 313): None

Precautions to be Taken in Handling and Storing: Ventilation in work area should be sufficient to maintain atmosphere with vapor level below lowest listed TLV in Section 2. If TLV's are exceeded, use a respirator with appropriate NIOSH approved cartridges or supplied air equipment. Keep containers closed when not in use. Combustible liquid - empty containers can be hazardous and contain explosive vapors.

The components of this product are listed on both the United States TSCA and the Canadian DSL.

HMIS: Health Hazard: 2 Flammability: 2 Reactivity: 0 Personal Protection: B

## **SECTION 8: CONTROL MEASURES**

Respiratory Protection: Needed if TLV's in Section 2 are exceeded. Use supplied air equipment or respirators with proper NIOSH approved cartridges.

Ventilation: Local and mechanical exhaust recommended. Avoid open electrical sources near product vapor areas.

Protective Gloves: Impervious or chemical resistant gloves (consult safety equipment supplier).

Eye Protection: Chemical splash goggles recommended.

Other Protective Clothing and Equipment: Safety shoes and aprons recommended.

Work and Hygiene Practices: Do not take internally. Avoid skin contact, and wash skin after using products. Do not eat, drink or smoke in work area. Keep away from children.

**FOR MORE INFORMATION, CONSULT TOWER PRODUCTS, INC.**

**THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIED IS MADE.**