



## Technical Data Sheet

### LO-VO WASH 50

#### LOW VOC ROLLER & BLANKET WASH

#### DESCRIPTION:

Formulated to meet the needs of printers who are attempting to reduce VOC's, LO-VO WASH 50 is an easy one-step method of cleaning. LO-VO WASH 50 contains less than 3.5 pounds per gallon of VOC's and can be mixed with water up to 50% to further reduce emissions. The product contains no reportable hazardous ingredients, has a flashpoint over 140 F and has a very mild odor.

#### DIRECTIONS FOR USE:

**BLANKETS:** Apply LO-VO WASH 50 full strength or diluted up to 50% with water, across the blanket. For best results, wipe off with a water dampened rag and buff dry. On web presses a water follow-up is not necessary since the web will dry the blanket. **ROLLERS:** Apply a small quantity (approximately 2-3 ounces) of LO-VO WASH 50 to the rollers. Allow press to idle for 20 seconds and engage the washup blade. Apply another 2 ounces of product followed by a water rinse, using about twice as much water as product. **PIPE ROLLERS:** Apply full strength. **READ MSDS BEFORE USE.**

#### FEATURES AND BENEFITS:

- \* High Flashpoint (142)
- \* Less than 3.5 pounds per gallon of VOC's.
- \* Does not contain water but can be mixed with water.
- \* Great cutting power and very low odor.

#### SPECIFICATIONS:

Flashpoint: Greater than 142 F TCC  
VOC: 3.45lbs. per gallon, 414 grams per liter, 50%  
Drying Speed: Slow  
Solvent Strength: Moderate  
Composite Vapor Pressure (mmHG): 5.0

#### HMIS INFORMATION

Health: 1 Flammability: 2 Reactivity: 0 Personal Protection: B

#### PACKAGING:

5 gallon pails and 55 gallon drums